






8156
brache per sollevamento 3t giallo nastro piatto a due strati, asole rinforzate, poliestere alta tenacità (PES)

CE

UNI EN 1492-1



| art. | art. | L m | | |
|-----------|-------------|--------|----|---|
| 081560010 | 8156 1-T3 | 1 | 90 | 3 |
| 081560015 | 8156 1,5-T3 | 1,5 | 90 | 3 |
| 081560020 | 8156 2-T3 | 2 | 90 | 3 |
| 081560025 | 8156 2,5-T3 | 2,5 | 90 | 3 |
| 081560030 | 8156 3-T3 | 3 | 90 | 3 |
| 081560040 | 8156 4-T3 | 4 | 90 | 3 |
| 081560050 | 8156 5-T3 | 5 | 90 | 3 |
| 081560060 | 8156 6-T3 | 6 | 90 | 3 |
| 081560080 | 8156 8-T3 | 8 | 90 | 3 |
| 081560100 | 8156 10-T3 | 10 | 90 | 3 |
| 081560120 | 8156 12-T3 | 12 | 90 | 3 |

| |  |  |  | $\beta=0^{\circ}+45^{\circ}$  | $\beta=45^{\circ}+60^{\circ}$  |
|-----|---|---|---|---|--|
| 30 | 1t | 0,8t | 2t | 1,4t | 1t |
| 60 | 2t | 1,6t | 4t | 2,8t | 2t |
| 90 | 3t | 2,4t | 6t | 4,2t | 3t |
| 120 | 4t | 3,2t | 8t | 5,6t | 4t |
| 150 | 5t | 4,0t | 10t | 7,0t | 5t |
| 180 | 6t | 4,8t | 12t | 8,4t | 6t |
| 240 | 8t | 6,4t | 16t | 11,2t | 8t |
| 300 | 10t | 8,0t | 20t | 14,0t | 10t |